



REVONFLOOR CLEAR RV 311 M

Epoxy Polyamide

PRODUCT DESCRIPTION	Solvent – based two pack epoxy polyamide medium.			
RECOMMENDED USE	Prepare floor repair and mortars undercoat.			
CHARACTERISTICS	• A hard wearing, good abrasion and impact resistance. • Solvent based, self – levelling, good resistance to wide spectrum of chemical. • Excellent adhesives to concrete, masonry, plasters and other building material.			
PHYSICAL DATA	Colour	Clear		
	Gloss Level	Gloss		
	Volume Solid	80%		
	Number of Coat	1		
	Theoretical Coverage	4 mm thick mortars 10.00 kg/sq.m		
	Mixing Ratio	Base : Hardener = 2 : 1		
	Thinner	Not required		
	Pack Size	20 Kgs		
	Shelf Life	12 months		
	Pot Life	1 hour at 32 ⁰ C		
	Temperature Resistance	93 ⁰ C (dry)		
	Flash Point	Base : 25 ⁰ C		
		Hardener : 48 ⁰ C		
	Drying Time			
	Substrate Temperature	Touch dry	Hard dry	To Top Coat
				Minimum Maximum
	30 ⁰ C	2 hours	12 hours	2 hours Indefinite
SURFACE PREPARATION	All surfaces to be coated should be clean, dry and free from contamination. Concrete Allow 28 days for concrete to cure. Remove surface laitance by acid etching, abrasive or scrapping, apply direct.			
APPLICATION DATA	Application Methods			
	Trowel	Recommended		
SAFETY PRECAUTION	<i>Keep away from heat, spark and Open flames. Avoid breathing of vapour on skin and eye contact. Keep container closed and store in cool, ventilated area when not in use. Proper ventilation and protective measures must be provided during mixing, application and drying, to keep vapour concentration within safe limits and to protect against topic hazard.</i> <i>Necessary safety equipment must be used and ventilation requirements carefully observed, especially in confined or enclosed spaces, such as tank interior and building.</i>			
DISCLAIMER	<i>The information in this product data sheet is given to the best of our knowledge based on laboratory testing and practical experience. If the product is used under condition beyond our control, we cannot guarantee anything but the quality of the products it self. The information in this product data sheet is liable for modification from time to time in the light of experience and our policy of continuous product development, and without further notice.</i>			